



### 12191

LOW PROFILE SIDE CLAMPING

#### Material

Steel hardened face.

#### Technical Notes

Designed to be used in the T-slots of machine tables.

The clamp has both a smooth face (for machined workpieces) and a serrated face (for rougher work). Provides a positive downhold action whilst maintaining a low profile.

#### Tips

Torque screw for T-slot nut to 150 Nm.  
\*Not supplied with T-nut or mounting screw.

| Order No.   | T-slot size | $l_1$ | $h_1$ | $h_2$ | $h_3$ | $h_4$ | $w_1$ | $w_2$ | Torque to Nm max. | Stroke $s_1$ | Holding force kN |
|-------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------------------|--------------|------------------|
| 12191.W0000 | *           | 50    | 25.4  | 22.2  | 15.7  | 9.6   | 28.5  | 25.4  | 88                | 1.6          | 17.8             |
| 12191.W0014 | 14          | 50    | 25.4  | 22.2  | 15.7  | 9.6   | 28.5  | 25.4  | 88                | 1.6          | 17.8             |
| 12191.W0016 | 16          | 50    | 25.4  | 22.2  | 15.7  | 9.6   | 28.5  | 25.4  | 88                | 1.6          | 17.8             |
| 12191.W0018 | 18          | 50    | 25.4  | 22.2  | 15.7  | 9.6   | 28.5  | 25.4  | 88                | 1.6          | 17.8             |

