



17008

SUPPORTS & STOPS

Material

Body: steel (C45), black oxide finish.
Piston: steel (C45), tempered, black oxide finish.

Technical Notes

The positive locking mechanism allows the

cap screw style to offer high support capacities.

Tips

When you attach a support tip to the tapped hole through the shaft, tighten the shaft and secure it to prevent damage.

Order No.	Type	h_1	h_2	d_1	d_2	d_3	d_4	Weight g
17008.W0033	Cap screw	33	22.0	28	14	-	M 6x12	150
17008.W0042	Cap screw	42	28.5	35	19	-	M 8x16	300
17008.W0050	Cap screw	50	34.0	42	22	-	M10x20	540
17008.W0060	Cap screw	60	42.0	50	26	-	M12x24	865
17008.W0070	Cap screw	70	47.0	60	33	-	M16x32	1390
17008.W0233	Thumb screw	33	22.0	28	14	24	M 6x12	185
17008.W0242	Thumb screw	42	28.5	35	19	30	M 8x16	360
17008.W0250	Thumb screw	50	34.0	42	22	36	M10x20	620
17008.W0260	Thumb screw	60	42.0	50	26	40	M12x24	1020

Order No.	d_5	d_6	l_1	l_2	Piston spring force N	Stroke s_1	Support capacity kN max.	Torque to Nm max.	A/F
17008.W0033	M 6x16	M 6	10	14.1	10~22	6	4.0	7.5	4
17008.W0042	M 8x20	M 8	15	18.8	10~27	10	6.0	14.0	5
17008.W0050	M10x25	M10	14	23.8	14~28	10	7.5	18.0	6
17008.W0060	M12x30	M12	17	28.5	15~30	10	9.0	22.0	8
17008.W0070	M12x30	M16	22	26.5	15~35	10	9.0	25.0	10
17008.W0233	M 6	M 6	10	22.7	10~22	6	0.6	1.0	4
17008.W0242	M 8	M 8	15	27.7	10~27	10	0.7	1.2	5
17008.W0250	M10	M10	14	31.8	14~28	10	0.7	1.5	6
17008.W0260	M12	M12	17	36.8	15~30	10	0.8	2.0	8

