



62000

PRECISION LEVELLING ADJUSTERS

Material

Steel (type 42 CrMo4 V, 1.7225) zinc plated or stainless steel A1 (A4 on request).

Technical Notes

After setting the height, the structure can be bolted down using a suitable 8,8

strength bolt.

The net load that the unit can carry is the maximum load less the tightening torque recommended for the bolt. Designed for applications with limited space. Height adjustment is between 4 and 10mm.

Order No.	Material	For bolt	h_1	h_2	h_3	d_1	d_2	d_3	Load with bolt kN max.	Load w/o bolt kN max.
62000.W0038	Steel	M 4	19	15	4	25	4.5	M15x1,0	36.00	40.0
62000.W0039	Steel	M 5	19	15	4	25	5.5	M15x1,0	33.40	40.0
62000.W0040	Steel	M 6	19	15	4	25	6.6	M15x1,0	30.70	40.0
62000.W0050	Steel	M 6	23	18	5	32	6.6	M20x1,0	55.70	65.0
62000.W0051	Steel	M 8	23	18	5	32	9.0	M20x1,0	48.00	65.0
62000.W0052	Steel	M10	23	18	5	32	11.0	M20x1,0	37.90	65.0
62000.W0070	Steel	M10	29	22	7	45	11.0	M30x1,5	92.90	120.0
62000.W0071	Steel	M12	29	22	7	45	13.5	M30x1,5	80.40	120.0
62000.W0072	Steel	M16	29	22	7	45	17.5	M30x1,5	45.50	120.0
62000.W0090	Steel	M16	37	28	9	58	17.5	M40x1,5	136.00	210.0
62000.W0091	Steel	M20	37	28	9	58	22.0	M40x1,5	90.00	210.0
62000.W0092	Steel	M24	37	28	9	58	26.0	M40x1,5	37.00	210.0
62000.W0100	Steel	M20	43	33	10	70	22.0	M50x1,5	210.00	330.0
62000.W0101	Steel	M24	43	33	10	70	26.0	M50x1,5	157.00	330.0
62000.W0102	Steel	M30	43	33	10	70	33.0	M50x1,5	53.00	330.0
62000.W0502	Stainless steel	M 4	19	15	4	25	4.5	M15x1,0	24.14	27.1
62000.W0503	Stainless steel	M 5	19	15	4	25	5.5	M15x1,0	22.24	27.1
62000.W0504	Stainless steel	M 6	19	15	4	25	6.6	M15x1,0	20.26	27.1
62000.W0550	Stainless steel	M 6	23	18	5	32	6.6	M20x1,0	36.56	43.4
62000.W0551	Stainless steel	M 8	23	18	5	32	9.0	M20x1,0	30.86	43.4
62000.W0552	Stainless steel	M10	23	18	5	32	11.0	M20x1,0	23.41	43.4
62000.W0570	Stainless steel	M10	29	22	7	45	11.0	M30x1,5	64.01	84.0
62000.W0571	Stainless steel	M12	29	22	7	45	13.5	M30x1,5	54.82	84.0
62000.W0572	Stainless steel	M16	29	22	7	45	17.5	M30x1,5	28.90	84.0
62000.W0590	Stainless steel	M16	37	28	9	58	17.5	M40x1,5	92.90	148.0
62000.W0591	Stainless steel	M20	37	28	9	58	22.0	M40x1,5	59.08	148.0
62000.W0592	Stainless steel	M24	37	28	9	58	26.0	M40x1,5	20.30	148.0
62000.W0600	Stainless steel	M20	43	33	10	70	22.0	M50x1,5	136.08	225.0
62000.W0601	Stainless steel	M24	43	33	10	70	26.0	M50x1,5	97.30	225.0
62000.W0602	Stainless steel	M30	43	33	10	70	33.0	M50x1,5	20.60	225.0

